

Fatigue crack detection in orthotropic steel deck bridges applied by FMC/TFM using reflected waves of multiple paths (1)

**Hirokazu Karasawa¹, Hiromi Shirahata², Shigeyuki Hirayama³, Shin Matsumoto⁴,
Hideo Isobe¹, Tomonari Kodama⁵, Masanobu Nagai⁶**

¹Inspection Devices Development & Production Department, Toshiba Inspection Solutions Co., Japan,
¹Facility of Architecture and Urban Design, Ltd., Japan, ¹Institute of Structural Technology, Tokyo City University, Japan, ¹Inspection Devices Development & Production Department, Shutoko Technology Center, Japan, ¹Inspection Devices Development & Production Department, Ltd., Japan, ¹West Tokyo Bureau Civil Engineering Maintenance Design Division, Metropolitan Expressway Company Limited, Japan

We introduce the latest developed FMC/TFM (Full Matrix Capture and Total Focusing Method) and its application for fatigue crack detection in orthotropic steel deck bridge. This developed inspection system consists of the advanced high-speed ultrasonic inspection equipment and the remotely operated four-wheel scanner with a 32-channel ultrasonic array probe for angle beam inspection. We developed MP-FMC/TFM (Multiple Paths Phased-array FMC/TFM) in this project. MP-FMC/TFM enables to visualize outline image of cracks clearly by image synthesis based on the propagation route information of direct path and the other paths reflected on the bottom of an inspection object against clacks. This developed inspection system enables to generate clear B-scope images of deck plate crack and bead (in deck-to-rib weld) crack with high-resolution. Furthermore, it enables to synthesizes 3D images of crack propagation with high-resolution along the weld line in real time by integrating the B-scope images every time the scanner moves 2mm. As a result of verification test of fatigue crack propagation test specimens, it was confirmed that this inspection system enables to visualize crack shape clearly and to achieves measurement accuracy of $\pm 0.8\text{mm}$ for depth of deck plate crack, and $\pm 1.0\text{mm}$ for depth of bead crack. Currently, verification tests are being conducted on an actual bridge, and practical application is planned in near future.